



MODEL	HI-S940T	HI-S940T-A	HI-S940T-Y
Görüntü Sensörü	1/3 SONY SUPHER HAD	SONY S.Hd II DupleSCAN	Enhanced SONY Effio-E system
Çözünürlük	580 TVL	600 TVL	650 TVL 700 TVL
PIXEL	PAL: 752(H) x 582(V) , NTSC: 768 (H) x 494(V)	PAL:795 (H) x 596 (V) NTSC:811(H) x 508(V)	
DWDR	YOK	EVET	
OSD MENÜ	YOK	EVET	
W/BL	EVET		
S/N ORANI	48-50 -52 dB		
IR ETKİ	36 ADET 850 NM HIGH LED 60 METRE IR ETKİ		
Lens	2,5mm ~ 12 MM AYARLANABİLİR 2 MEGA PIXEL VARIFOCAL LENS		
Ölçüleri	290 X110 X 110 MM		
Isısı /Nem	-20°C ile 50°C (0°C to 40°C RH)		
Ağırlık	1000 GRM – IP 66 -67		
GECE/GÜN.	TRUE (GERÇEK) DAY NIGHT GECE GÖRÜŞLÜ		
Mirror	YOK	EVET	
Mask	YOK	EVET	
BLC	OTOMATİK	EVET	
AGC	OTOMATİK	EVET	
ATW	YOK	EVET	
HLC/HLVI	YOK	EVET	
Baudrate	YOK	2400-9600-4800	
CRT LCD	YOK	EVET	
Alarm	YOK	EVET	
2 3D NOISE	YOK	EVET	
HR.ALGILA	YOK	EVET	
ELEKTRİK	12VDC (50Hz/60Hz) Led AÇIK I 800 mA		